REPORT NO: J20017832-231

REPORT DATE: AUGUST 21, 2000

PAGE 1 OF 4

CLIENT: AMERICAN METAL PRODUCTS INC.

MODEL: DIRECT VENT GAS APPLIANCE VENT TERMINALS

TEST REPORT NO. J20017832-231

EVALUATION
OF
MODELS 4DHC, 5DHC, 4DVC, 5DVC, 4DWT AND 5DWT
DIRECT VENT APPLIANCE VENTING COMPONENTS

FOR AMERICAN METAL PRODUCTS 8601 HACKS CROSS ROAD OLIVE BRANCH, MI 38654

BY
INTERTEK TESTING SERVICES NA INC
8431 MURPHY DRIVE
MIDDLETON, WISCONSIN 53562

INTRODUCTION

Intertek Testing Services NA Inc. (ITS) of Middleton, Wisconsin, examined and tested the above stated direct vent appliance venting components manufactured and furnished by American Metal Products of Olive Branch, Michigan. The tests were conducted on May 15 – June 14, 2000 for compliance with applicable sections of ANSI Z21.88-1999•CSA 2.33-M99 "Standard for Vented Gas Fireplace Heaters." The vent components were tested in conjunction with Johnson Gas Appliance Co. models SDV-40, DXV-42, and Chateau 60 direct vent gas fireplace heaters. The results in this report are limited to the items submitted. The test data is on file at ITS, Middleton, Wisconsin.

All services undertaken are subject to the following general policy: Reports are submitted for exclusive use of the clients to whom they are addressed. Their significance is subject to the adequacy and representative character of the samples and to the comprehensiveness of the tests, examinations, or surveys made. No quotations from reports or use of the Intertek Testing Services NA (ITS) name, logo, or registered (WHI) mark is permitted except as expressly authorized by Intertek Testing Services NA Inc. in writing.



REPORT NO: J20017832-231 REPORT DATE: AUGUST 21, 2000

CLIENT: AMERICAN METAL PRODUCTS INC.

MODEL: DIRECT VENT GAS APPLIANCE VENT TERMINALS

PAGE 2 OF 4

PRODUCT DESCRIPTION

The models stated below are venting components for gas-fired direct vent appliances. They are concentric (coaxial) pipes for separating the inlet and exhaust gases. A complete description of the components including proprietary drawings is on file at ITS, Middleton, Wisconsin.

Description	Part Number	Materials	Diameter Dimensions (in)
Vertical termination	4DVC	Stainless steel/galvanized steel	4 by 6-5/8
Vertical termination	5DVC	Stainless steel/galvanized steel	5 by 8
Horizontal termination	4DHC	Stainless steel/galvanized steel	4 by 6-5/8
Horizontal termination	5DHC	Stainless steel/galvanized steel	5 by 8
Wall Thimble	4DWT	Stainless steel/galvanized steel	4 by 6-5/8
Wall Thimble	5DWT	Stainless steel/galvanized steel	5 by 8

CONSTRUCTION REVIEW

ANSI Z21.88-1999 • CSA 2.33-M99

SECTION	SUBJECT/REQUIREMENT	RESULTS
1.1	Scope	Informational
1.2	General Construction	Complies
1.3	Accessibility	Complies
1.4	Thickness of Materials	Complies
1.5	Evaluation of Comb./Venting Side Sealing Materials	Complies
1.6 - 1.23	Appliance Specific Sections	Not applicable
1.24	Direct Vent/Air Intake Pipes	Complies
1.25 - 1.35	Appliance Specific Sections	Not applicable

REPORT NO: J20017832-231

REPORT DATE: AUGUST 21, 2000

PAGE 3 OF 4

CLIENT: AMERICAN METAL PRODUCTS INC.

MODEL: DIRECT VENT GAS APPLIANCE VENT TERMINALS

PERFORMANCE

ANSI Z21.88-1999 • CSA 2.33-M99

SECTION	SUBJECT/REQUIREMENT	RESULTS
2.1 - 2.3	General, Appliance Specific	Informational
2.4	Combustion	Complies
2.5	Appliance and Burner Durability Test	Complies
2.6	Burner Operating Characteristics	Complies
2.7	Loose Materials	Not applicable
2.8	Pilot Operating Characteristics	Complies
2.9 - 2.11	Appliance Specific Sections	Not applicable
2.12	Delayed Ignition & Integrity Tests for Direct Vent App.	Complies
2.13 - 2.20	Appliance Specific Sections	Not applicable
2.21	Wall, Floor and Ceiling Temperatures	Complies
2.22 - 28	Appliance Specific Sections	Not applicable
2.29	Wind Tests	Complies
2.30	Vent & Vent/Air Intake Terminal Assembly	Complies
2.31 - 2.36	Appliance Specific Sections	Not applicable

TEST EQUIPMENT

Test equipment used to measure and record data was as follows. Calibration records are on file at ITS - Middleton, Wisconsin.

- 1. Gordon type K (Chromel Alumel) thermocouple wire and Type J (iron constantan) thermocouple wire, special limits type.
- 2. Omega Digital/Analog thermocouple readouts (Type K and J).
- 3. Omega 16, 20, and 40 position J/K switching modules.
- 4. Horiba Model PIR-2000 Carbon Monoxide Analyzer, WHI #70.
- 5. Horiba Model PIR-2000 Carbon Dioxide Analyzer, WHI #306.
- 6. Rockwell Model T-110 Dry Gas Meter, WHI #14.
- 7. Rosemount Model 755R Oxygen Analyzer, WHI #364.

CLEARANCES TO COMBUSTIBLES

At the conclusion of testing, the wall thimble and vent terminals were found acceptable for zero-clearance to combustibles when installed per the manufacturer's instructions.

REPORT NO: J20017832-231

REPORT DATE: AUGUST 21, 2000

PAGE 4 OF 4

CLIENT: AMERICAN METAL PRODUCTS INC.

MODEL: DIRECT VENT GAS APPLIANCE VENT TERMINALS

CONCLUSIONS

Based on tests conducted with Johnson Gas Appliance models SDV-40, DXV-42, and Chateau 60 direct vent gas fireplace heaters, the American Metal Product models 4DHC, 5DHC, 4DVC, 5DVC, 4DWT and 5DWT appliance vent components are deemed in compliance with ANSI Z21.88-1999•CSA 2.33-M99 when used in conjunction with all Johnson Gas Appliance direct vent gas fireplace heater models. The vent components are to be constructed and installed in accordance with ITS approved documentation. This report does not automatically imply certification. Products must bear a WHI label in order to demonstrate certification.

Tested by:

William Keen

Engineering Technician

Reviewed and reported by:

Edwin Hodgson Project Manager